

2.8 Tubes for GAS conduction .High Density Polyethylene PIPES PE 100.

Application: Underground conduits of gaseous fuels.
Standard: UNE-EN 1555
MOP: SDR 17.6: Maximum Operating Pressure 4 bar -
SDR 11: Maximum Operating Pressure 10 bar
Color: SDR 17.6: Yellow-Orange or black yellow-orange bands
SDR 11: Black with Yellow-Orange stripes
Marking: According to Norm
Availability: - In rolls of 50 m DN 63 and 90
- In bars of 6, 8 or 13 m from DN 90 to 315



DN/OD Mm	Format: Rolls or bars / palet 6 ó 12 m SDR 17.6 / 11	SDR 17,6		SDR 11	
		Thickness mm	Price €/m	Thickness mm	Price €/m
20	rolls			3.0	0,94
32	rolls			3.0	1,61
40	rolls			3.7	2,49
63	rolls	3.6	3,97	5.8	6,10
90	rolls or 95 bars	5.2	8,17	8.2	12,33
110	60 bars	6.3	12,06	10.0	18,28
160	28 bars	9.1	25,27	14.6	38,79
200	19 bars	11.4	39,45	18.2	60,48
250	12 bars	14.2	61,40	22.7	94,14
315	8 bars	17.9	97,25	28.6	149,40

- For other dimensions, lengths, color or types, please consult us